edu.mit.csail.aeolus.auditing
Class EventID

```
java.lang.Object
  └ edu.mit.csail.aeolus.auditing.EventID
```

All Implemented Interfaces:
AeolusSafe, java.io.Serializable, java.lang.Cloneable

```
public final class EventIDextends java.lang.Objectimplements java.io.Serializable, AeolusSafe, java.lang.Cloneable
```

User/system event ID associated with a log record

See Also:
Serialized Form

Field Summary

static EventID	**systemEvent** **Deprecated.**

Method Summary

EventID	**clone**() Returns a new EventID which will be equal to this.
boolean	**equals**(java.lang.Object e)
int	**hashCode**()
java.lang.String	**toString**()

Methods inherited from class java.lang.Object

finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

systemEvent

```
@Deprecatedpublic static final EventID systemEvent
```

Deprecated.

Method Detail

clone

```
public EventID clone()
```

Returns a new EventID which will be equal to this.

Overrides:
`clone` in class `java.lang.Object`

---

equals

```
public boolean equals(java.lang.Object e)
```

Overrides:
`equals` in class `java.lang.Object`

---

hashCode

```
public int hashCode()
```

Overrides:
`hashCode` in class `java.lang.Object`

---

toString

```
public java.lang.String toString()
```

Overrides:
`toString` in class `java.lang.Object`